



**TPC**

Tabriz Petrochemical Company

**Address :**

**Azarshahr Road , Next  
to the tabriz Refinery  
Tabriz , Iran**

**Po. BOX: 51745 - 354**

**Tel: [+98(0)411]4280000**

**FAX:**

**Tel: [+98(0)411]4201487**

**HD -5218UA  
High Density polyethylene**

**- Product Description**

- HD-5218UA is a high density polyethylene copolymers containing butane-1 as the co-monomer with narrow molecular weight distribution, suitable for thin wall injection application. It has been designed for fast cycling application and low warpage with a good balance of toughness and stiffness characteristics.

**- Applications**

- Houseware
- Thin walled containers
- Food container
- Toys
- Home utensil

**- Typical Data**

Property	Test Method	Unit	Typical Value
Physical Properties			
MFI(190°C/ 2.16Kg)	ASTM D 1238	gr/10Min	18.0
MFI(190°C / 5.0Kg)			52.0
Density	ASTM D 1505	gr/cm³	0.952
Formulation			
Anti Oxidant		√	
Slip Agent		-	
UV Stabilizer		√	
Mechanical Properties			
Flexural Modulus	ASTM D 790	MPa	1050
Tensile Strength at yield	ASTM D 638	MPa	20
Elongation at Break	ASTM D 638	%	900
Charpy Impact Strength	ASTM D 256	Kj/m²	3
Hardness Shore D	ASTM D 2240	-	65
Thermal Properties			
Vicat Softening Temperature	ASTM D 1525	°C	115
Melting Point	ASTM D2117	°C	131