

SEETEC EVA VA900

Ethylene Vinyl Acetate Copolymer

Lotte Chemical Corporation

PROSPECTOR®

www.ulprospector.com

Technical Data

Product Description

SEETEC VA900 resin is produced by ExxonMobil Chemical's autoclave process technology.

SEETEC VA900 resin, with 28% VA content, is an excellent raw material in the application of hot melt adhesives.

General

Material Status	• Commercial: Active		
Literature ¹	• Technical Datasheet (English)		
Search for UL Yellow Card	• Lotte Chemical Corporation • SEETEC EVA		
Availability	• Asia Pacific	• Europe	• North America
Additive	• Antioxidant		
Features	• Antioxidant		
Uses	• Adhesives		
RoHS Compliance	• RoHS Compliant		

Physical	Nominal Value Unit	Test Method
Density	0.950 g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	150 g/10 min	ASTM D1238
Vinyl Acetate Content	28.0 wt%	Internal Method
Hardness	Nominal Value Unit	Test Method
Durometer Hardness (Shore D)	21	ASTM D2240
Thermal	Nominal Value Unit	Test Method
Vicat Softening Temperature	< 40.0 °C	ASTM D1525
Melting Temperature	67.0 °C	Internal Method

Notes

¹ These links provide you with access to supplier literature. We work hard to keep them up to date; however you may find the most current literature from the supplier.

² Typical properties: these are not to be construed as specifications.



SEETEC EVA VA900

Ethylene Vinyl Acetate Copolymer

Lotte Chemical Corporation

PROSPECTOR®

www.ulprospector.com

Where to Buy

Supplier

Lotte Chemical Corporation

Seoul, Seoul South Korea

Telephone: +82-2-829-4114

Web: <http://english.lottechem.com/>

Distributor

Advanced Plastics, Inc

Telephone: 847-550-5556

Web: <http://www.apikolon.com/>

Availability: Mexico, North America, South America

RESINEX Group

RESINEX is a Pan European distribution company. Contact RESINEX for availability of individual products by country.

Telephone: +32-14-672511

Web: <http://www.resinex.com/>

Availability: Europe

