

POLYPROPYLENE
DAPC-HP550P

Description:

"DAPC-HP550P" is a high melt flow polypropylene homopolymer for the production of BCF, CF and fine denier staple fibers at medium to high spinning speeds.

"DAPC-HP550P" is suitable for nonwoven fabrics for diapers, medical-sanitary applications and wipes. Another typical application is high tenacity continuous filament for straps backpacks, sport bags, bulk bags and safety belts. Continuous filament whit medium tenacity is used for upholstery and sportswear. "DAPC-HP550P" is also suited for the production of bulked continuous filament for carpets.

Processing Method:

Fiber Extrusion (BCF, CF, Staple)
Injection molding

Features:

High melt flow
Good processability
Homopolymer


Typical Applications:

Wipes and tissues
Straps for backpacks, sport bags, bulk bags and for safety belts
Upholstery and sportswear
Bulk continuous filament for carpets
Nonwoven staple fiber
Injection molded article, housewares, etc.

TYPICAL PROPERTIES	ASTM / METHOD	VALUE	UNIT
Physical			
Melt Flow Rate (230 °C, 2.16kg)	D1238	21	g/10min
Density	D1505	0.90	g/cm ³
Mechanical			
Flexural Modulus	D790	1550	MPa
Tensile Strength at Yield	D638	33	MPa
Tensile Elongation at Yield	D638	12	%
Izod Impact Strength (notched) at 23 °C	D256	30	J/m
Thermal			
Vicat softening point (10N)	D1525	154	°C
H.D.T. (0.46 MPa)	D648	95	°C
Accelerated oven ageing in air at 150 °C	D3012	120	hours

➤ Values shown are averages & are not to be considered as product specifications

Address: No: 89, West Nahid St., Nelson Mandela Blvd, Amaneyeh – Tehran, 1966913435, Iran
Tel: +982122049507
Email: info@diariapolymer.com
Web site: www.diariapolymer.com



PRC-1401-066-Rev 01